







Jet Air Boy®

High blowing force, unblockable and low noise level

Blowgun equipped with a Jet Air 1 flat nozzle

The Jet Air Boy® combines all the best features. It is silent with only 81,5 dB at 8 bar and complies with OSHAs and EU's requirements in regards to noise level. The blowing force is high with 580 l/min. / 5,05 N at 8 bar, compared to most of the low noise level blowguns on the market. The construction of the nozzle secures that the nozzle is unblockable and therefore complies with OSHA STD 1-13.1 requirements.

The ergonomic design is a classic in itself. We use the compressed air to ease the activating of the handle making it easy, accurate and simple to operate.

The Jet Air Boy® is produced in an impact-resistant acetal plastic (POM)





Newton (g) / bar(psi)

The durability of our blowguns is top notch - even after 28 million operations. Therefore, we are also proud to offer you a 25 year warranty on the valve system in your Air Boy® blowgun!

Blowing force

dB / bar(psi)

Materials		Specifications			Directives				
Handle and trigger	Acetal plastic	P	Max 8 bar		2003/10/CE	Max 85 dB	OK		
Valve	Acetal plastic		580 l/min (8bar)		OSHA 1910.95 (b)	Max 90 dB 8 hr	OK		
Gaskets / O-rings	Nitrile		81,5 dB (8 bar), (78 db at 6 bar)	0	OSHA STD 1-13.1	Max 30 psi when blocked	OK		
Blowing tube & shaft	Acetal, Steel		-10°C to +80°C						
Spring	Hardened spring wire		~0,095 kg						

Flow	l/min(cfm) / bar(psi
600 (21,19) 500 (17,66) 400 (14,13) 300 (10,59) 200 (7,06) 100 (3,53)	1 2 3 4 5 6 7 8 (15) (29) (44) (58) (73) (87) (102) (116)

100 🛨		
100 T		
90 -	Measured at a distance of m to the side of the nozzle	
80 -		81,5
		78
70 -		
60 -		
50		
_	1 2 3 4	5 6 7 8
	1 2 3 4 (15) (29) (44) (58)	(73) (87) (102) (116)

Noise level

6 (612) 5 (510)	Measu distan	red on a	400 x 4	00mm	plate at	ta		5,05
4 - (408) 3 -							3,73	
2 - (204) 1 -								
(102)	1 (15)	2	3 (44)	4 (58)	5 (73			3