




Air Boy® Classic

Robust, impact-resistant and leakage free

Blowgun with bent pipe, ø8mm

The Air Boy ergonomic design is a classic in itself. We use compressed air to ease the activation of the handle making it easy, precise and simple to operate.

The Air Boy® Classic is produced in an impact-resistant acetal plastic (POM).





The durability of our blowguns is top notch - even after 28 million operations. Therefore, we are also proud to offer you a 25 year warranty on the valve system in your Air Boy® blowgun!

Materials		Specifications			Directives			
Handle and trigger	Acetal plastic	P	Max 16 bar		2	003/10/CE	Max 85 dB	OK
Valve	Acetal plastic		380 l/min (8 bar)		0	SHA 1910.95 (b)	Max 90 dB 8 hr	OK
Gaskets / O-rings	Nitrile		85 dB (8 bar), 84 dB (6 bar)	OSHA STD 1-13.1		Max 30 psi when blocked	-
Blowing tube & shaft	Steel, el. galvanised		-10°C to +80°C					
Spring	Hardened spring wire		~0,105 kg					
Flow	l/min(cfm) / bar(psi)	Noise level dB /		dB / bar(psi)	Blow	ing force	Newton (g) / ba	r(psi)
600 (21,19) 500 (17,66) 400 (14,13) 300		100 90 Measured at a distance of 1m to the side of the nozzle 80 80 80 84			6 (612) 5 (510) Measured on a 400 x 400mm plate at a distance of 150 mm from the nozzle 4 (408) 3 2,84			



200 (7,06) 100 (3,53)