

124140128 Silent Air Boy® Pressure Stop







Silent Air Boy®

Low noise level and unblockable

Blowgun with bent pipe, ø8mm

The Silent Air Boy® combines all the best features. It is silent with only 74 dB at 8 bar and complies with OSHAs and EU's requirements in regards to noise level. The construction of the nozzle secures that the nozzle is unblockable and therefore complies with OSHA STD 1-13.1 requirements.

The ergonomic design is a classic in itself. We use the compressed air to ease the activating of the handle making it easy, accurate and simple to operate.

The Silent Air Boy® is produced in an impact-resistant acetal plastic (POM).






The durability of our blowguns is top notch - even after 28 million operations. Therefore, we are also proud to offer you a 25 year warranty on the valve system in your Air Boy® blowgun!

Materials			Specifications			
Handle and trigger	Acetal plastic	P	Max 16 bar			
Valve	Acetal plastic		260 l/min (8bar)			
Gaskets / O-rings	Nitrile		74 dB (8 bar), (72 db at 6 bar)			
Blowing tube & shaft	Steel, el. galvanised		-10°C to +60°C			
Spring	Hardened spring wire		~0,1020 kg			
Flow	l/min(cfm) / bar(psi)	Noi	se level di			
600 (21,19)		10	00			

100 -	asured a to the si		nce of e nozzle	Ъ_			
80 -							74
70 -						71,6	/4
60 -							
50 -							
L		2	3 .	4 :	5 (5 :	3

	Directives								
	2003/10/CE	Max 85 dB	OK						
	OSHA 1910.95 (b)	Max 90 dB 8 hr	OK						
ar)	OSHA STD 1-13.1	Max 30 psi when blocked	ОК						
dB / bar(psi)	Blowing force	Newton (g) / bar	(psi)						



400 (14,13) 300 (10,59)

200

100

3 4