



COMPRESSOR 100

Industrial Lubricant

ISO 100

Code:170COIL100

COMPRESSOR 100 is a premium air compressor lubricant formulated from selected highly stable base stocks, with a special non hydrolysing anti wear additive to allow compressors to continue operating under the most severe conditions.

SPECIFICATIONS

COMPRESSOR 100 meets or exceeds the following specifications.

- ISO 100

APPLICATIONS

COMPRESSOR 100 is suitable for all reciprocating compressors that specify an ISO 100 grade.

COMPRESSOR 100 gives longer valve cleaning intervals due to its high resistance to deposit formation and outstanding oxidation stability. Minimal wear is also achieved as a result of excellent rust protection and high film strength. Long service life of up to 4000 hours in reciprocating compressors.

COMPRESSOR 100 can also be used as hydraulic oil, turbine oil and circulation oil where the application calls for a non zinc type oil where there are pumps with silver plated surfaces.

COMPRESSOR 100 results in a finished product which is minimum deposit forming, has long life, protects compressor components from wear and also separates readily from water ingress.

TYPICAL MAIN CHARACTERISTICS

CHARACTERISTICS	ISO 100
Viscosity at 40 C, (cSt)	100
Viscosity at 100 C,(cSt)	11.3
Density	0.88
Viscosity Index	106
Flash Point deg C	210
Pour Point deg C	-9
C.C. Residue %	0.9

PACKAGE SIZE 1, 4, 20 & 205 Litre

Due to continual product research and development, the information contained herein is subject to formulation change without notice.

Values stated are average values only and may vary due to manufacturing tolerances.