

VW FRONT SUSPENSION SILENT BLOCK EXTRACTION /

INSTALLATION TOOL KIT (W/ HYDRAULIC CYLINDER)





 The ET1544A pulling device allows the quick and safe removal and installation of assembly carrier double-type silent blocks on the vehicle. Loosening or removing the assembly carrier from the vehicle as well as follow-up wheel alignments is not necessary.

• Applications:

Applications.		
Make	Model	Year
Audi	A3 (8P1)	05/2003 onwards
Audi	TT (8J3, 8J9)	from 08/2006 to 06/2010
Seat	Altea (5P5, 5P5, 5P8)	03/2004 onwards
Seat	Leon (1P1)	05/2005 onwards
Seat	Toledo III (5P2)	from 04/2004 to 05/2009
Skoda	Octavia (1Z3, 1Z5)	from 02/2004 to 12/2010
VW	Caddy III (2KA, 2KB, 2KH, 2KJ, 2CA,	from 04/2004 to 08/2010
	2CB, 2CH, 2CJ)	
VW	EOS (1F7, 1F8)	06/2006 onwards
VW	Golf Plus (5M1, 521)	01/2005 onwards
VW	Golf V (1K1, 1K5)	from 10/2003 to 2009
VW	Golf VI (5K1, AJ5)	10/2008 onwards
VW	Jetta III (1K2)	from 08/2005 to 10/2010
VW	Touran (1T1, 1T2, 1T3)	08/2003 onwards
VW	Passat (3C2, 3C5, 362, 365)	from 03/2005 to 06/2010
VW	Scirocco (137)	05/2008 onwards
VW	Tiguan (5N)	09/2007 onwards
	•	•

;

Note !



Lines

- When installing, put part #10 in the middle of the bushing to fix its position.
- When bushings connect with part No. 5, the gaps of bushings need to put in the middle of the two lines.



- After installing, part #10 needs to be taken out.
- Do not forget!!