

24

Inspection Light Flexible

LED-186



Integrated

Dual head worklight 5W COB on each side
use both together or separately as needed

User controlled output

Adjust light intensity from 50-500 lumens (on each light) by rotating knob

| | 1ST PRESS | 2ND PRESS | 3RD PRESS |
|----------|--------------------|-------------------|----------------|
| | FRONT WORKLIGHT | BACK WORKLIGHT | BOTH LIGHTS |
| LUMEN | 500 | 500 | 1000 |
| RUN TIME | 2-16 hours | 2-16 hours | 1-8 hours |

Sturdy Construction

a. IP 54 Rated

Protected against dust and effects of water spray from any direction

b. IK 07 Rated

Impact proof ABS body

c. Sturdy polycarbonate lens to withstand the toughest of job site conditions

d. Nylon hook with ratcheting mechanism can be rotated full 360° for convenient placement of light as required

e. Built-in magnet on top of the light to pickup small metallic parts

Direct light as needed

Heavy-duty flexible neck can be rotated & bent 360° horizontally & vertically

Hands Free Operation

Strong magnet on base for direct attachment on any metallic surface

Charging of Battery

- Type C fast charging protected by rubberized bezel.
- Charge indicated by 3 LED's, each showing 33% of battery

Dual head
worklight
5W COB on
each side



CE
RoHs
IP54
IK07


Intensity
control knob

Hook

ORDERING INFORMATION

| CAT NR. | ORD NR. | SIZE (L×H×D) | | BOX QTY. |
|------------|------------|----------------------------|-------------------|-------------|
| | | (INCH) | (MM) | |
| LED/186 | 55114 | 16-21/32 × 2-37/64 × 1-3/4 | 423 × 65.5 × 44.5 | 10 |

POWER SOURCE



3.7V 2600 mAh

