

- Light duty 12 Watt, for general purpose of soldering
  Charging time 3.5 hours
  One charge provides 90 minutes continuous use
  LED illumination on your application
  Max. temperature goes up to 932°F[500°C]
  Reaches working temperature 356°F[180°C] in 10 seconds
  Charging board protection:
  Overcharging/Overdischarging/Short circuit/ESD



Designed & Manufactured by Pro-Iroda Industries, Inc.





## PLEASE READ INSTRUCTIONS CAREFULLY BEFORE OPERATING.

## A WARNING:

- Potential electrical shock. Do not use soldering iron if housing is cracked or damaged. Never use in wet area. Do not attempt to repair or modify soldering iron. Always de energize device being soldered.
   Potential burn hazard. Hot tip can cause severe burns. Do not touch tip of tool. Allow tool to cool before touching tip or replacing protective cap.
   When used for soldering and similar applications, this product contains or produces chemicals known to the State of California to cause cancer and birth defects or other reproductive harm.

1M USB to micro USB cable and safety stand included.

## Specifications:

PRO-25-SI Soldering Iron	ron no
Dimensions	H-210mm
	L-30mm
	W-23mm .
Weight(w/o gas filled)	100g
Charging Time	3.5 Hours
Running Time	Approx. 90Minutes
Max.Temperature	500°C/932°F